



US006637705B2

(12) **United States Patent**
Sjoblom et al.

(10) **Patent No.:** **US 6,637,705 B2**
 (45) **Date of Patent:** **Oct. 28, 2003**

(54) **FLOW METER STRUT**

(75) **Inventors:** **Byron G. Sjoblom**, Middletown, RI (US); **Gary R. Berlam**, Cambridge, MA (US)

Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(* **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 10/051,520

(22) **Filed:** Jan. 22, 2002

(65) **Prior Publication Data**

US 2003/0136883 A1 Jul. 24, 2003

(51) **Int. Cl.⁷** **F16L 3/22**

(52) **U.S. Cl.** **248/68.1; 248/49; 248/127; 248/161**

(58) **Field of Search** **248/68.1, 49, 127, 248/146, 161, 172, 176.3, 122.1, 125.1, 125.2, 343, 906, 200.1; 211/857; 73/201, 272 R, 273, 195**

References Cited

U.S. PATENT DOCUMENTS

2,322,753 A * 6/1943 Thomas 128/221
 3,770,031 A * 11/1973 Olson 144/136
 4,061,298 A * 12/1977 Kober 278/677
 4,154,100 A * 5/1979 Harbaugh et al. 73/861.66
 4,237,739 A * 12/1980 Owen et al. 73/861.63
 D278,316 S * 4/1985 Bengtson D10/96
 4,552,270 A * 11/1985 Lentz et al. 211/17
 4,637,175 A * 1/1987 Froening et al. 52/27
 4,696,194 A * 9/1987 Taylor 73/861.66

4,723,747 A * 2/1988 Karp 248/298
 4,813,550 A * 3/1989 Sacks 211/17
 4,972,339 A * 11/1990 Gabrius 362/366
 4,995,288 A * 2/1991 DellaPolla 83/574
 5,086,930 A * 2/1992 Sacks 211/17
 5,337,615 A * 8/1994 Goss 73/861.33
 5,386,959 A * 2/1995 Laughlin 248/205.1
 5,394,781 A * 3/1995 Tsubai 83/449
 D358,952 S * 6/1995 Stein D6/466
 5,996,945 A * 12/1999 Coles et al. 248/68.1
 6,012,340 A * 1/2000 Pounder 73/861.77
 6,033,098 A * 3/2000 Hentz 362/430
 6,206,613 B1 * 3/2001 Elkins 405/157
 6,389,909 B1 * 5/2002 Johnson et al. 73/861.78
 6,401,555 B1 * 6/2002 Bowers 73/866.5
 6,422,092 B1 * 7/2002 Morrison et al. 73/861.04
 D464,582 S * 10/2002 Pepperling et al. D10/96

OTHER PUBLICATIONS

U.S. Ser. No. 2002/0144557 to Drahm Electromechanical Transducer, Oct. 2002.*

* cited by examiner

Primary Examiner—Korie Chan

Assistant Examiner—Amy J. Sterling

(74) **Attorney, Agent, or Firm**—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) ABSTRACT

A flow meter strut assembly includes a strut portion having a first end plate, a second end plate, a longitudinally adjustable flow meter support structure between the first and second end plates, and curved mounting surfaces formed on outer surfaces of each of the first and second end plates of the strut portion. At least one flow meter is adjustably mounted on the flow meter support structure. The flow meter support structure is adjustable longitudinally by a turnbuckle assembly connected between the flow meter support structure and the second end plate.

6 Claims, 1 Drawing Sheet

